

TITEBOND® ALL WEATHER SUBFLOOR ADHESIVE

PHYSICAL PROPERTIES

Type: Synthetic elastomeric polymer
State: Medium-viscosity mastic
Color: Light tan
Solids: 67%
Viscosity: 130,000 cps

Calculated VOC (less water): 389 g/L
Weight/gallon: 9.81 lbs.
Flashpoint: Less than 0°F.
Freeze/thaw stability: Will not freeze
Storage life: 12 months in tightly closed containers at 75°F.

APPLICATION GUIDELINES

Application temperature: 0°F. to 100°F.
Service temperatures: -20°F. to 120°F.
Method of application: Cartridge/caulking gun
Coverage (maximum): Approximate length of bead according to bead diameter:

Container	1/8" bead	1/4" bead	3/8" bead
10.5 oz. Cartridge	129 ft.	32 ft.	14 ft.
29 oz. Cartridge	355 ft.	89 ft.	39 ft.

Working time: Approximately 10-20 minutes for a 1/4" bead

Working surfaces: Surfaces to be bonded should be clean and free from excessive oil, grease, water, dirt or any other material that may deter adhesion. Apply adhesive to each piece of furring, studs or floor joists to be covered. When bonding subfloors or wet, frozen and treated lumber, nail or screw each sheet as recommended by the American Plywood Association.

Cleanup: Scrape off dried excess with a putty knife. Remove residue with mineral spirits or equivalent solvent. Follow solvent vendor's precautions when using solvents. NOTE: Test solvent on an out-of-the-way area to make sure it will not mar or attack the surface.

PRODUCT FEATURES

- Works extremely well in colder temperatures
- Ideal for plywood, particleboard, OSB, and wet, frozen and ACA & CCA treated lumber
- Fills gaps and irregularities between materials to provide a more solid backup surface
- Exceeds the performance requirements of the American Plywood Association AFG-01 Specification, ASTM D3498, ASTM C557, CAN/CGSB-71.26M and CAN/CGSB-71.25M

LIMITATIONS

Titebond All Weather Subfloor Adhesive is not designed for continuous submersion or for use on polystyrene foams. For polystyrene foam, tub surrounds and most other plastics, we recommend Titebond Interior/Exterior Construction Adhesive.

CAUTION STATEMENT

DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL. Contains hexane and toluene. Keep away from heat, sparks and flame. Use only with positive cross-ventilation. Avoid breathing vapors. Do not swallow. Do not allow eye contact or prolonged skin contact. Uncured product can cause eye or skin irritation. Prolonged or repeated overexposure to solvents in uncured product can cause central nervous system, peripheral nervous system, eye, skin, liver, kidney or respiratory system effects. **FIRST AID:** If dizziness or other adverse effects are experienced, move to fresh air; call physician if discomfort persists. If eye contact occurs, flush eyes with water for 15 minutes; contact physician immediately. If swallowed, do not induce vomiting; contact physician immediately. Wash skin contact areas with soap and water; contact physician if irritation persists. For additional information, refer to Material Safety Data Sheet. **KEEP OUT OF THE REACH OF CHILDREN.**

WARNING: This product contains toluene, a chemical known to the State of California to cause birth defects or other reproductive harm.

ORDERING INFORMATION

Cat. No.	Size	Units per Package	Weight	Packages per Pallet
45492	29 oz. Mini Pallet	144 tubes	352	12
5491	10.5 oz. Cartridge	12	11	108
5492	29 oz. Cartridge	12	30	38

Important Notice: Our recommendations, if any, for the use of this product are based on tests believed to be reliable. Since the use of this product is beyond the control of the manufacturer, no guarantee or warranty, expressed or implied, is made as to such use or effects incidental to such use, handling or possession or the results to be obtained, whether in accordance with the directions or claimed so to be. The manufacturer expressly disclaims responsibility therefore. Furthermore, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing laws and/or patents covering any material or use.

2020 Bruck Street, Columbus, Ohio 43207
 CUSTOMER SERVICE 1-800-669-4583
 TECH SERVICE 1-800-347-GLUE
 www.titebond.com

Franklin International
 ©2008 Franklin International. All rights reserved.